Switch assembly-console moulding



Before repairing any electrical parts, starting switch power mode must be set to OFF state, and all electrical loads must be OFF, unless otherwise specified in the operation procedure. If any tool or equipment is easy to contact any exposed live electrical terminal, disconnect the negative battery cable, too. Any violation of these safety instructions may result in personal injuries or damages to the vehicle and its components.

NOTE

- There might be some differences on illustrations of this program, and you are advised to the vehicle configuration, but the basic information is always correct.
- There might be some parts that are not displayed on the illustration. That will help display the main parts more clearly.

Removal




Be sure to use a tool made of plastic or similar materials when removing the switch.


- 1. Remove the console moulding switch panel assembly-front. See: Console moulding switch panel assembly-front
- 2. Remove the two mounting screws on the console moulding switch panel assembly-rear.




3. Remove the console moulding switch panel assembly-rear.




4. See the figure below for the position of the clip on the console moulding switch panel assembly-rear.



5. Disconnect the console moulding switch harness connector and remove the console moulding switch panel assembly-rear.



6. Remove the six mounting screws of the console moulding switch assembly and then remove the console moulding switch assembly.



Installation



When installing the interior trim, please confirm that the interior trim claw is aligned with the mounting position, and then press the interior trim gently to prevent damage to the interior trim jaw.

- 1. Install the console moulding switch assembly. Install the six mounting screws on the console moulding switch assembly.
- 2. Connect the console moulding switch harness connector and install the console moulding switch panel assembly rear.
- 3. Install the two mounting screws on the console moulding switch panel assembly-rear.
- 4. Install the console moulding switch panel assembly-front.Console moulding switch panel assembly-front

() NOTE

If new module has been installed, please carry out the matching/writing/calibration with the diagnosis devices approved by AIWAYS.